

Duo-Therm Part No.	Filter Drier (1)	MFR (2)	MANUFACTURER MODEL NUMBER	Manufacturer's Ratings (3)			Run Capacitor		Start Capacitor	
				BTU Capac.	Volts-PH-HZ	Amps.	MFD.	VOLTS	MFD.	VOLTS
3-2749	3	C	RRF2-0100-PAA	10,800	115-1-60	10.8	25	370	64-77	330
3-2750	3	C	RRD2-0101-PAA	7,075	115-1-60	8.7	15	370	43-53	220
3-6610	1	C	JRG4-0100-PAA	9,400	115-1-60	10.4	15	370	43-53	220
3-7593	1	T	AK5510E(AK100AT005)	10,000	115-1-60	10.5	25	370	21-25	220
1307885	16	T	AK5511E(AK110AT005)	11,000	115-1-60	11.0	25	370	64-77	330
1308183	16	C	JRJ4-0075-PAA	7,100	115-1-60	7.9	15	370	43-53	220
1308184	16	C	JRL4-0100-PAA	11,000	115-1-60	11.0	25	370	43-53	220
1309318	B	C	RRK4-0126-PAA	13,500	115-1-60	14.4	30	370	64-77	250
1316344	16	F R	K48A49B-001 K48A131B*-002	13,500	115-1-60	12.5	20	370	47-56	250
1316369	16	F R	K48A04B-002 K48A111A*-005	11,000	115-1-60	10.5	25	330	47-56	250
1316438	16	C	JRR4-0100-PFA	12,000	115-1-60	12.2	25	330	43-53	330
1316443	16	F R	K39A38-002 K39A711D*-003	7,100	115-1-60	8.1	25	330	21-25	220
1316966	16	C	RRH4-0151-PAZ	13,000	220/240-1-50	7.8	20	370		
1317348	16	C	REB3-0150-PFJ	12,750	220/240-1-50	6.9	25	370		
1318085	16	S	80680442/C-R80H2G	11,000	115-1-60	9.5	35	330	43-53	250
1318086	16	S	80608042/C-R100H2G	13,500	115-1-60	12.2	20	370	25-30	330
1318163	16	R	K48B133A*-005	13,200	220/240-1-50	7.1	30	440	47-56	250
1318435	16	R	H48A131B*-002	13,500	115-1-60	12.5	25	330	47-56	250
1318670	16	R	H48A111A*-002	11,000	115-1-60	10.8	25	330	47-56	250
3100223.019	16	R	H48A133C*-102	13,500	220/240-1-50	6.2	35	370	47-56	250
3100224.017	16	R	H48A783A*-102	7,800	220/240-1-50	4.0	17.5	370	47-56	250

* MAY BE EITHER O OR S.