SPECIFICATIONS

MODEL NO.		600312.321	600315.321
Nominal Capacity (BTU/HR)		11,000	13,500
Electrical Rating		115 VAC, 60 Hz., 1 ph.	
Compressor Rated Load Amps		9.5	12.4
Fan Motor Rated Load Amps		3.1	3.1
Compressor Locked Rotor Amps		53.0	60.0
Fan Motor Locked Rotor Amps		8.8	8.8
Input Watts- Cooling		1350	1600
SCFM-High Speed Max./Min.		335/250	
Total Static - Min./Max.		0.12 / 0.65" W.C.	
Refrigerant (R22) Oz.		16.5	15.5
Minimum Wire Size ***		12 AWG Copper Up to 24 ft.	
AC Circuit Protection		20 Amp Time Delay Fuse or HACR Circuit Breaker	
Installed Weight (Pounds)			95 96
Minimum Generator	1 Unit	2.5KW	3.5KW
Size **	2 Units	4.0KW	5.0KW

* For distances over 24 ft. consult the National Electrical Code.

** The Dometic Corporation gives general guidelines for generator requirements. These guidelines come from experience people have had in actual applications. When sizing the generator, the total power usage must be considered. Also keep in mind generators lose power at high altitudes and from lack of maintenance.