

## Brite-Ply Roof Care & Maintenance

Proper care and maintenance of your recreational vehicle, including your Brite-Ply roof, is important for trouble-free performance. Normal maintenance is simple, easy, and requires no special equipment.

- 1) Keep your roof clean. Clean your roof at least (four) 4 times annually. For normal cleaning:
  - Use Dicor's Rubber Roof Cleaner ready to use RP-RC320S or concentrated RP-RC160C ( see CAUTION below)
  - Rinse complete roof with clean water to remove any loose dirt or debris.
  - Using a medium bristle brush, along with the cleaner mixed with water, scrub the entire roof. Rinse thoroughly with clean water to avoid residue build-up on the roof or sidewalls of the vehicle.
  - For more difficult stains, you may use Dicor's RP-RC160C, mentioned above, in a more concentrated mixture.

Recommended Dicor cleaners: RP-RC320S (ready to use) and  
RP-RC160C (concentrated).

**CAUTION: DO NOT use cleaners or conditioners containing petroleum solvents, harsh abrasives, or citric based cleaners. You may cause irreparable damage to your roof.**

**Use Caution when working on top of your vehicle. The wet Brite-Ply membrane may be extremely slippery.**

- 2) Be aware of areas where fruit, tree sap or harsh environment fall-out may stay on the roof for an extended period of time. These conditions may result in unremovable stains. If you are in these conditions, you may have to increase the frequency of your cleaning or premature deterioration may occur.