

### 12v QUICK 'N' EZ AND 12v QUICK 'N' EZ XL

#### 12 VOLT QUICK 'N' EZ ORDERING INFORMATION & SPECIFICATIONS

**SIZES AVAILABLE: 12' 13' 14' 15' 16' 17' 18' 19' 20' 21' 22' 23' 24' 25'**

**EXTENSION AVAILABLE: 8' or 9'8" (XL)**

---

#### QUICK 'N' EZ TIPS, FACTS, AND COMMONLY ASKED QUESTIONS:

---

##### THE 12V QUICK 'N' EZ:

- Available in two models, regular with 8' ext., or XL with 9'8" ext. and have different part numbers. Be certain to confirm correct part numbers.
- Available as a complete awning or as an upgrade to existing Carefree awnings with an 8' extension. An upgrade is not available for the XL model.
- Does not have springs. If you are upgrading a traditional awning, you will need to remove the springs from the roller tube.
- Awning is measured center of arm to center of arm. Note: the wiring receptacle must be installed through the side of the RV at a point 3" to 5" below the awning rail and 1" to 4" to the left of the front arm assembly. Be sure to account for any obstacles.
- Canopy is always 10" shorter than size ordered.
- Standard extension of 8' is available in all fabrics and colors. The XL LTD. model (9'8" extension and acrylic fabric) is available only in solid or vertical stripe Sunbrella acrylic fabrics. Consult your Sunbrella swatch book for patterns.

##### 12V QUICK 'N' EZ ARMS:

- Is similar to the Carefree ONE-Touch awning except the 12V Quick 'N' EZ arms come with handles that allow for a manual pitch, rain release setting. The motorized roller extends out and then the customer manually adjusts the arms.  
**Important note:** The arms must be manually returned to the lowest stop bolt position prior to retracting the awning.
- Measurement for arms, both models, awning rail to bottom bracket is 68" to 81".  
**WARNING:** Only order XL if your awning rail is 11' or higher off the ground. At 11' the lowest setting on the roller when extended is 6'5".
- Custom colored options are available for the arms and alumaguard.
- Upgrading from a Carefree manual awning? Purchase only the 12V Quick 'N' EZ arms.
- Operates on 12 Volt power and requires a dedicated 15 Amp circuit.
- Amp draw: 4.7 minimum, 8 Amp maximum when locking.
- WindSmart auto retract kit is not available for the 12V Quick 'N' EZ.

##### ORDERING:

**You will need to know the following information:**

- Is this a complete new awning or upgrade?
- The size and extension of the awning.
- Canopy color, choice of fabric, weatherguard or alumaguard color choice.
- Determine regular or XL arms. For XL insure awning rail is 11' off the ground.
- Color of arms including any custom colored options.

##### WARRANTY:

##### **Carefree Two & Four Year Limited Warranty**

- Two Years 100% on canopy, parts, labor, freight. Four Years, 100% parts, labor and freight on roller assembly, motor, electronics, and hardware from manufacturer defects.

##### SHIPPING:

- Cannot be shipped UPS. Applicable freight surcharges apply.