



Sensar III for RV

RV-3095 SENSAR III AMPLIFIED DIRECTIONAL RV TV ANTENNA, "CABLE READY"

[Check out our SENSAR III Accessories & Replacement Parts](#)



The Hand Crank Assembly is located inside your unit to raise, lower and rotate the Sensar for best RV TV reception.

**US Patent No.
5262793**

The 75 ohm Sensar RV-3095 antenna has built-in amplifier and unique circuitry that gives you clear VHF/UHF reception whenever you park your RV. Raise, lower and rotate the Sensar III antenna from inside your parked RV. It's easy to install and extends only four inches above the roof while traveling. The antenna can be elevated to 40" above the roof line, and is bidirectional — it must be pointed toward the TV station you want to watch. It must be used while the vehicle is parked. The Sensar antenna is made of tough UV protected Centrex®* polymer and other materials that are corrosion resistant.

Sensar® model RV-3095 includes 20 feet of 75 ohm coaxial cable, 6 foot TV set cord, mounting hardware and a white on/off power supply switch. Switch has +12VDC receptacle, built-in two-way splitter for second TV outlet, a convenient power-on/off indicator light and cable TV input. For exterior RV TV/cable outlet, order WA or WT series weatherproof outlets. Standard elevating tubes 36", includes RV-7042 power supply.



SENSAR III TV ANTENNA SPECIFICATIONS (Model RV-3095)

Height lowered	4 inches	Impedance	75 ohm
Height raised	40 inches	Amplifier Gain	VHF 15.5 dB average
Width	antenna only 4.75 inches		UHF 19.5 dB average
Length	antenna including elements 45.5 inches	Power required	12VDC at 85 ma

Shipping Weight	12 pounds	
-----------------	-----------	--

**Also available as Model RV-7005,
bulk pack of four includes antenna, manual lift.**

Does not include power supply, coax cable, or interior control parts.



RV-5095

RV-5095 NON-AMPLIFIED SENSAR III

This 75 ohm non-amplified version of the RV-3095 can be used all types of recreational vehicles. The RV-5095 is designed for years of reliable service. Includes antenna, lift assembly, rotating handle, elevating crank assembly, and 15 feet of 75 ohm coaxial cable. The RA-7596 wallplate amplifier strengthens signal for non-amplified antennas.



RV-7095

RV-7095 SENSAR III AMPLIFIED

The RV-7095 includes only the amplified antenna and lift with white interior control parts. Power supply & coax not included.

Click [here](#) for the Sensar III manual.

© 2003 Winegard Company. All Rights Reserved